

Manufactured by:
 Mat-Nu-Wood L.L.C.
 a subsidiary of:

Mat-RCP Mat-RCP Plus

Mat Inc.
 12402 Hwy 2
 Floodwood, MN 55736



Recycled Clean Paper Mulch


Produced in Lenoir, North Carolina.

888-477-3028

Fax: 218-476-2039
 matinc@matinc.biz

Quality Erosion Control Products

Manufactured by Mat Ag-Fiber L.L.C. a subsidiary of



Mat-RCP[®]


100% Recycled Clean Paper Mulch For Hydraulic Planting.

Net Wt.
 50 lbs.
 22.6kg.

Mat-RCP[®]


Mat-RCP

100% Recycled Clean Paper Mulch For Hydraulic Planting



Net Wt.
 50 lbs.
 22.6kg.

Manufactured by Mat Ag-Fiber L.L.C. a subsidiary of



Mat-RCP[®]

100% Recycled Clean Paper Mulch With Added Tackifier For Hydraulic Planting.

Plus

Net Wt.
 50 lbs.
 22.6kg.

Mat-RCP[®]



Mat-RCP Plus[®]

100% Recycled Clean Paper Mulch With Added Tackifier For Hydraulic Planting

Net Wt.
 50 lbs.
 22.6kg.

Mat-RCP[®]

98% Recycled Clean Paper Mulch

Mat-RCP Plus[®]

97% Recycled Clean Paper with 3% added tackifier

Ingredients:

Recycled clean paper content.....	98%
Basic green dye.....	<1%
Trade secret.....	<1%

Composition:

Organic matter (min.).....	90%
Inorganic matter (ash) (max.).....	10%
Moisture content (total weight base).....	12% ± 3%
pH at 3% consistency in water slurry (avg.).....	6.55
Water-holding capacity (min.).....	1.2gal./lb.

Ingredients:

Recycled clean paper content.....	95%
Tackifier content by weight.....	3%
Basic green dye.....	<1%
Trade secret.....	<1%

Composition:

Organic matter (min.).....	90%
Inorganic matter (ash) (max.).....	10%
Moisture content (total weight base).....	12% 3%
pH at 3% consistency in water slurry (avg.).....	6.55
Water-holding capacity (min.).....	1.2gal./lb.

Where to use Mat-RCP[®]

- Basic Lawn and Turf applications.
- Slopes of 4:1 or flatter
- Application ranges of 1500 to 2000 pounds to the acre. (max.)
- Straw tacking or as a temporary ground cover.
- Where fast mixing and pumpability are desired.

Where to use Mat-RCP Plus[®]

- Basic Lawn and Turf applications.
- Slopes of 3:1 or flatter
- Application ranges of 1500 to 2000 pounds to the acre. (max.)
- Straw tacking or as a temporary ground cover.
- Where fast mixing and pumpability are desired.

Packaged in 50lb. (22.5kg.) plastic bags available in palletized 40 bag units
Product certification and SDS available upon request.

For more information call Mat. Inc. Customer Service
 1-888-477-3028 or visit our website at: www.matinc.biz